# DDR3 SIGNATURE LINE 4GB PC3-12800 (1600MHZ) UNBUFFERED DIMM





facebook.com/patriotMEM



twitter.com/patriotmemory



#### 50 Word Description:

Patriot Memory's Signature Line DDR3 Non-ECC Unbuffered memory delivers the quality, reliability and performance expected for today's computer needs. These 4GB modules are designed to run at PC3-12800 (1600MHz) at CAS 11 latency timings. Built using specific build-of-materials (BOMs) we ensure that every module meets and exceeds industry standards: offering you a hassle-free upgrade.

#### 100 Word Description:

Patriot Memory's Signature Line DDR3 Non-ECC Unbuffered memory delivers the quality, reliability and performance expected for today's computer needs. These 4GB modules are designed to run at PC3-12800 (1600MHz) at CAS 11 latency timings. Built using specific build-of-materials (BOMs) we ensure that every module meets and exceeds industry standards: offering you a hassle-free upgrade. We certify every component that goes into our modules, including the modules themselves, which must pass strict standards to ensure compatibility, quality and reliability. With free customer service and a lifetime warranty, Patriot Memory's Signature memory modules are a perfect system upgrade option.

## PRODUCT INFORMATION

Product Name	Signature Line
Description	PSD34G160082
Patriot Part #	Patriot Signature 4GB DDR3 PC3-12800 (1600MHz) CL11 DIMM
Certifications / Safety	RoHS
Product Warranty	Lifetime Warranty
Unit Dimensions	.25" (D) x 5.27" (W) x 1.15" (H) .64 cm (D) x 13.4 cm (W) x 2.9 cm (H)
Unit UPC	814914023112
Packaging Type	Blister Pack
Packaging Dimensions	.63" (D) x 4.64" (W) x 7.08" (H) 1.6 cm (D) x 5.3 cm (W) x 16.5 cm (H)
Net Weight	.02 lbs / 16.5 gm .04 lbs / 89 gm (with heatshield)
Gross Weight	.08 lbs / 25.5 gm .07 lbs / 113.5 gm (with heatshield)
Units per Inner Carton	25
Units per Master Carton	250

### **FEATURES**

- PC3-12800 (1600MHz) dual Data Rate
- 240-Pin Dual in-line memory module
- Non-ECC Unbuffered
- 2 Rank module
- 7.8US Refresh Interval (8192 CYCLES/64MS)
- · 1.5V Power Requirement
- · Auto and self refresh capability
- PCB height: 1181(mil)
- Serial Presence-Detect (SPD)
- 100% Tested
- · RoHS Compliant
- Compatible with Intel® 6 Series or later and AMD 9 Series/FM Series or later.